INSPECTION CHAMBER With Hinges



GROUP 2

Footways, pedestrian and comparable areas, car parks or car parking decks.







Standard

EN124-2:2015 / Class B125

Material

EN 1563 - Grad GJS-500/7

Pattern

Design of cover pattern allows for special Logo or project design to be inserted in its specified area on the cover.

Square/Rectangular cover with hinges and anti-slippery surface, single seal.


Non ventilated cover to prevent vitiated air spreading from underground to the outside.




Applied Bitumen coat according to BS 3416 or Epoxy Paint.



All manhole covers are marked with the following: (Name of Manufacturer - En124 Class Load and Material)





INSPECTION CHAMBER With HINGES					GGG DUCTILE CAST IRON APPLICATION
Туре	Art. No.	Over base	Clear Open	Height	Coating
Square	IC-G2-D-15001	520x520	400x400	42	Black Bitumen
Rectangular	IC-G2-D-15002	720x520	600x400	42	Black Bitumen
Square	IC-G2-D-15003	720x720	600x600	42	Black Bitumen
Square	IC-G2-D-15004	920x920	800x800	42	Black Bitumen
Square	IC-G2-D-15005	1160x1160	1000×1000	42	Black Bitumen
				ı	All Dimensions in mm

